

# 全自动皮带送料冲裁精密四柱油压裁断机

## Fully Automatic Full Belt Feeding Precision Hydraulic Cutting Machine

HG-B60T, HG-B80T, HG-B100T, HG-B120T, HG-B150T

适用于裁切EPE泡棉包装、隔音棉、塑料薄膜、多层麻布等薄形材料

Used for die cutting EPE foam packaging, soundproof products, plastic film, multi-layer fabric etc thin materials.



### 特点：

- > 自动皮带在线送料以及移动夹具出料，整个送料、裁断、出料过程自动化，节省劳力。
- > 滚筒装置带有自动卷料控制功能，可快速整理卷材；可快速更换滚筒。
- > 可编程序逻辑控制器控制及触屏式显示屏，可设定和控制工作压力，裁断深度和送料速度，操作更加简单精确、快速。
- > 双油缸，四柱加上平衡连杆的自动平衡结构，保证每个裁断位置裁断深度完全相同。

### Features:

- > Automatic roller belt feeding, movable clamp out-feeding, allows all cutting process without any labor.
- > Roller device with auto rolling function to roll materials easily; rollers easy to change.
- > Controlled by PLC(Programmable Logic Controller), with touching screen, to adjust working pressure, stroke, feeding speed easier, faster and more precise.
- > Auto-balance structure of double-cylinder, four-column and sett-balance connecting rod, makes sure equal pressure in any working area.

型号 Model	裁断力 Cutting Force	体积 Dimension	裁断区域 Cutting Area	马达 Motor	冲程 Stroke	净重 Net Weight
HG-B60T	60 Tons	3700X2350X1900 mm	810X1600 mm	5.5 kw	50-230 mm	4500 kg
HG-B80T	80 Tons	3700X2350X1900 mm	810X1600 mm	7.5 kw	50-230 mm	5000 kg
HG-B100T	100 Tons	3700X2350X1900 mm	810X1600 mm	7.5 kw	50-230 mm	5500 kg
HG-B120T	120 Tons	3700X2350X1900 mm	810X1600 mm	11 kw	50-230 mm	6000 kg
HG-B150T	150 Tons	3700X2350X1900 mm	810X1600 mm	11 kw	50-230 mm	6500 kg

说明：裁断力50吨到300吨可选·裁断区域、电压可按需提供。

Remark: cutting force can be from 50 tons to 300 tons; cutting area can be 610/710/810/910x1400/1600/1800mm, etc